


Environmental Improving Equipment

Spot Cooler

Specifications

Make	SUIDEN			AIRREX	DAIKIN
Model	SS-22DD-8A	SS-40DC-8A	SS-56EG2-8B	HSC-2500	TTIM560B2
Power Supply	1 Phase - AC200V			1 Phase - AC220V	3 Phase - 380V
Power (W)	800	1,650	2,430	6,150	62,000
Temperature	25°C~45°C			20°C~22°C	15°C~43°C
Dimensions W×D×H (mm)	390x430x808	470x520x1,120	490x600x1120	490x600x1,280	1,950x2,100x1,735
Weight (kg)	37	71	92	86	1,040
Outlet Number	1	2	3	2	1

※ Rental Item : Extend Exhaust Duct 5m



DAIKIN



SUIDEN




AIRREX



Extend Exhaust Duct

Humidity	Ambient temperature	Cool air temperature	
80%	38℃	31.6℃	→ -6.4℃
	35℃	28.4℃	→ -6.3℃
	32℃	25.1℃	→ -6.9℃
60%	38℃	28.0℃	→ -10.0℃
	35℃	25.5℃	→ -9.5℃
	32℃	22.4℃	→ -9.6℃
40%	38℃	25.3℃	→ -12.7℃
	35℃	22.6℃	→ -12.4℃
	32℃	20.2℃	→ -11.8℃



Infrared Heater



Specifications

Model	VAL6 KBE1S
Heat Output	28,000kcal / 32.5kw
Fuel	Diesel
Tank Capacity	35ℓ
Power Source	230V
Power Consumption	60W
Dimension (HxWxD)	810mm×655mm×695mm
Dry Weight	38kg

Dehumidifier



ID-12000S



RFB-500F



DM-15V

Specifications

Model	ID-12000S	RFB-500F	DM-15V
Dehumidification (L/H)	50	1.4	1.4
Temperature (°C)	1~40	1~40	1~40
Voltage (V)	380	200	200
Power (kW)	14.16	0.54	0.54
Dimensions L×W×H (mm)	2,500×600×1,800	858×377×407	835×430×390
Weight (kg)	610	36	33